

# Nitrogen PSA Generators NITROSWING® NS-125



## Typical Applications

- Blanketing of Chemicals and Pharmaceuticals
- Gas Assisted Injection Molding (GAIM)
- Heat Treatment of Ferrous & Non-Ferrous Metals
- Inerting of Flammable Liquids
- Laser Cutting
- Prevention of Dust Explosions
- Re-flow and Wave Soldering of PCBs
- UV-Curing of Coatings


## Advantages of NITROSWING® PSA's

- **Safety:** Low Operating Pressures, no Hazardous Storage
- **Economy:** Low Operating Cost, Easily Expandable
- **Convenience:** Fully Automatic and Unattended Operation
- **Reliability:** Easy to Install and Maintain

## The Nitrogen Production Process

IGS Nitrogen PSA Generators separate nitrogen (N<sub>2</sub>) from compressed air utilizing pressure swing adsorption technology. Compressed air, which consists of approximately 21% oxygen and 78% nitrogen, is passed through a bed of carbon molecular sieve (CMS). The sieve preferentially adsorbs O<sub>2</sub> and moisture over N<sub>2</sub> allowing the N<sub>2</sub> to pass through as a product gas at pressure. While one of the towers is in the adsorption phase the other tower is regenerated by de-pressurizing at which time the sieve releases the adsorbed gases to the atmosphere and the cycle is then repeated.

A solid state programmable controller operates the process valves on an alternating cycle with built-in logic for automatic stop/start. Nitrogen flow and purity remain constant regardless of the peak usage demands. Under normal operating conditions and with correct maintenance the carbon molecular sieve will have an almost indefinite lifetime.



### Standard Components

- Air Filters
- Adsorber Vessels
- Pneumatic Valves
- Piping and Instrumentation
- Safety Valve
- Exhaust Muffler
- Nitrogen Pressure and Flow Regulator
- Control System with Allen-Bradley PLC
- Skid Mounted
- Pressure Switch for automated Idle-Mode
- Hour Meter

### Options

- Oxygen Analyzer (Zirconium Oxide type)
- Dew Point Analyzer
- Product Flow Meter
- Fail Safe Package (off-spec nitrogen automatically vented to atmosphere\*)
- Enhanced PLC with Telemetry
- Purities to 99.9999% with a De-Oxo System
- Feed Air Compressor
- Product Booster Compressor
- Monitor Package (with indication of Feed Air and Product Pressures and Temperatures, Oxygen Concentration and Product Flow on AB PanelView\*\*)
- Air Receiver Tank
- Nitrogen Buffer Tank
- Bottle Filling Station

\* Only in combination with Oxygen Analyzer Option  
\*\* Includes Oxygen Analyzer and Flow Meter

## NITROSWING NS-125L Series Specifications & Performance

Standard	SI 7.5 Bar(g) feed pressure and 21° C					US 109 PSIG feed Pressure and 70° F				
Oxygen %	Nitrogen Nm <sup>3</sup> /h	Nitrogen Pressure Bar (g)	Feed Air Nm <sup>3</sup> /h	Air Receiver Liters <sup>(3)</sup>	Nitrogen Receiver Liters <sup>(3)</sup>	Nitrogen SCFH	Nitrogen Pressure PSIG	Feed Air SCFH	Air Receiver Gallons <sup>(3)</sup>	Nitrogen Receiver Gallons <sup>(3)</sup>
3	215	5.5	432	1,818	4,819	7,595	80	15,272	400	1,060
2	190	5.7	409	1,818	4,819	6,701	83	14,428	400	1,060
1	156	6.0	369	1,818	4,819	5,510	87	13,020	400	1,060
0.5	135	6.1	378	1,818	3,000	4,765	88	13,346	400	660
0.1	72	6.2	279	1,818	1,818	2,532	90	9,866	400	400
0.05	55	6.2	256	1,818	1,818	1,952	90	9,028	400	400
0.01	42	6.2	229	1,818	1,091	1,489	90	8,093	400	240
0.005	33	6.2	223	1,818	909	1,158	90	7,868	400	200
0.001	23	6.2	197	1,818	909	809	90	6,942	400	200
Dew Point <sup>(2)</sup>	-40°C / -40°F									
Sound Level	< 85 dB(A)									

## NITROSWING NS-125H Series Specification & Performance

Standard	SI 10 Bar(g) feed pressure and 21° C					US 145 PSIG feed Pressure and 70° F				
Oxygen %	Nitrogen Nm <sup>3</sup> /h	Nitrogen Pressure Bar (g)	Feed Air Nm <sup>3</sup> /h	Air Receiver Liters <sup>(3)</sup>	Nitrogen Receiver Liters <sup>(3)</sup>	Nitrogen SCFH	Nitrogen Pressure PSIG	Feed Air SCFH	Air Receiver Gallons <sup>(3)</sup>	Nitrogen Receiver Gallons <sup>(3)</sup>
3	286	8.0	576	1,818	7,046	10,112	116	20,333	400	1,550
2	271	8.2	583	1,818	7,046	9,560	119	20,582	400	1,550
1	203	8.5	480	1,818	4,819	7,170	123	16,942	400	1,060
0.5	151	8.6	423	1,818	4,819	5,332	125	14,932	400	1,060
0.1	78	8.7	304	1,818	1,818	2,758	126	10,747	400	400
0.05	64	8.7	294	1,818	1,818	2,247	126	10,390	400	400
0.01	52	8.7	283	1,818	1,818	1,838	126	9,992	400	400
0.005	36	8.7	248	1,818	1,091	1,287	126	8,743	400	240
0.001	27	8.7	232	1,818	909	956	126	8,204	400	200
Dew Point <sup>(2)</sup>	-40°C / -40°F									
Sound Level	< 85 dB(A)									

### Connections

Connections available in ANSI Flange, DIN Flange or NPT

### Approximate Weight and Dimensions

L	W	H	Weight
1,372	1,372	2,870 mm	1,632 kg
54	54	113 in.	3,597 lb

### Power Requirements

Power Supply 110-230 V / 50-60 Hz  
Power Consumption max. 0.3 kW

*Consult IGS for specifications on specific model and desired options.*

### Notes:

- (1) Flow rates at standard atmospheric conditions (70 °F, 14.7 psi / 20 °C, 1013 mbar and 60% RH)
- (2) Dew point at atmospheric pressure.
- (3) Receiver size is recommended minimum capacity. Smaller receiver volumes will result in lower product pressures. Please contact IGS for details.
- (4) NITROSWING PSA nitrogen generators can be configured for use in food processing and packaging applications however, it is recommended that you consult IGS before purchasing a generator for any food application.
- (5) Min. Air Quality: ISO 8573.1 / Class 1.4.1, improver feed air quality may cause damage to the nitrogen generator not covered under warranty.
- (6) Other pressures and purities available, consult IGS for specifications.
- (7) IGS reserves the right to change data without notice.
- (8) Only in case of an on-board installation of an oxygen analyzer and/or product flow meter.



**Generon IGS**  
16250 Tomball Parkway  
Houston, Texas 77086  
(713) 937-5200

E-Mail: [igssales@igs-global.com](mailto:igssales@igs-global.com)  
Internet: [www.igs-global.com](http://www.igs-global.com)

